

# **SF Coatings Safety Data Sheet**

#### **Product and Company Information** 1.

**Product Information** 

Product Name: SF Epoxy Crack Repair Part A

Product Type: **Epoxy Floor Coating** 

Date MSDS Prepared: 07/01/2015 03/01/2012 Supersedes:

MSDS Prepared by: jrc **Company Information** 

SF Coatings

717 Riverside Dr SE North Bend, WA 98045 Information: 425-888-5565

\*\*\* 24 Hour Emergency Phone Number: Infotrac: 1-800-535-5053 \*\*\*

#### 2. **Hazards Identification**

Emergency Overview: Skin sensitizer. Repeated exposure may cause rash or other allergic reaction. Eye irritant. Will not permanently damage eye tissue. Inhalation irritant. May cause respiratory tract irritation, headache, and dizziness. High vapor concentrations may cause bronchitis, coughing, chest pain, and depression of central nervous system. Harmful if swallowed. May cause vomiting and diarrhea, unconsciousness with convulsions.

#### **GHS Classification:**

Acute toxicity (oral) Category 4 Skin corrosion/irritation Category 2 Skin sensitization Category 1 Chronic aquatic toxicity Category 2

#### **GHS Label Elements:**

#### **Hazard Symbols:**





Signal Words: Warning

#### **Hazard Statements:**

H302 Harmful if swallowed H315 Causes skin irritation H317 May cause an allergic skin reaction H411 Toxic to aquatic life with long lasting effects

#### **Precautionary Statements:**

P261 Avoid breathing dust/fume/gas/mist/vapours/spray Prevention:

SF Coatings, Inc. SDS: SDS SF Epoxy Crack Repair Part A.doc P264 Wash hands thoroughly after handling

P270 Do not eat, drink, or smoke when handling this product

P272 Contaminated work clothing should not be allowed out of the workplace

P273 Avoid release to the environment

P280 Wear protective gloves/protective clothing /eye protection/face protection

Response: P301+P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

P302+P352 IF ON SKIN: Wash with plenty of soap and water

P330 Rinse mouth

P333+P313 If skin irritation or rash occurs: get medical advice/attention

P362 Take off contaminated clothes and wash before reuse

P391 Collect spillage

Storage: Not applicable

Disposal: P501 Dispose of contents/container in accordance with local/regional/national regulation.

## 3. Composition/Information on Ingredients

| Ingredient                | Wt. Percent Range | CAS         |
|---------------------------|-------------------|-------------|
| Bisphenol A epoxy polymer | 50-65             | 25085-99-8  |
| Alkyl glycidyl ether      | 10-30             | 68609-97-2  |
| Acrylate monomer          | 5-15              | proprietary |
| Benzyl alcohol            | 5-15              | 100-51-6    |
| Silicon dioxide           | 0-5               | 112945-52-5 |

#### 4. First Aid Measures

**Skin Contact:** Remove contaminated clothing. Wash with soap and water. Seek medical attention if irritation occurs. Wash contaminated clothes separately before reuse.

**Eye Contact:** Remove contact lenses at once. Immediately flush with water for at least 15 minutes. Hold eyelids apart while rinsing. Seek medical attention if irritation persists.

**Inhalation:** Remove victim to fresh air. If not breathing, give artificial respiration. If symptoms persist, seek medical attention.

**Ingestion:** Do **NOT** induce vomiting. Get immediate medical attention. Never give something by mouth to an unconscious or convulsing person.

## 5. Fire Fighting Measures

Flash Point: 210°F (TCC) Flammable Limits: LEL = Not Established UEL = Not Established

**Extinguishing Media**: Use foam, carbon dioxide, dry chemical or water fog.

**Fire Fighting Procedures**: Full protective clothing and self contained breathing apparatus should be worn. Use water fine spray to cool containers.

Unusual Fire and Explosion Hazards: Closed containers can explode due to buildup of pressure.

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide.

#### 6. Accidental Release Measures

**Spill Response**: Ventilate the area. Contain spill if possible, preventing entry into sewers and waterways. Absorb with an inert material such as dry sand or earth and place in a chemical waste container for disposal. Avoid combustible materials such as sawdust. Avoid personal contact.

## 7. Handling and Storage

**Handling**: Handle in a manner to minimize personal contact.

**Storage**: Store at normal room temperature away from heat, sparks, and flames. Keep container tightly closed when not in use.

## 8. Exposure Control/Personal Protection

#### **Exposure Limits**

| Ingredient                | ACGIH TLV            | Oral LD 50      | Dermal LD 50    | Inhalation LC 50 |
|---------------------------|----------------------|-----------------|-----------------|------------------|
| Bisphenol A epoxy polymer | Not Established      | Not Established | Not Established | Not Established  |
| Alkyl glycidyl ether      | Not Established      | >4000 mg/kg     | >20,000 mg/kg   | Not Established  |
| Acrylate monomer          | Not Established      | Not Established | Not Established | Not Established  |
| Benzyl alcohol            | Not Established      | 1-3 g/kg        | 2 ml/kg         | 1000 ppm/8 hrs   |
| Silicon dioxide           | 10 mg/m <sup>3</sup> | >10 g/kg        | Not Established | Not Established  |

#### **Personal Protective Equipment**

**Skin**: Wear impervious gloves, clothing, and boots.

Eyes: Do not wear contact lenses. Wear safety glasses with side shield.

**Respiratory**: Not ordinarily required. When necessary, use a properly fitting NIOSH/MSHA approved respirator with organic vapor cartridge.

**Ventilation**: Provide adequate ventilation, particularly in confined areas.

Hygienic Practices: Wash face and hands thoruoghly before eating or drinking..

## 9. Physical and Chemical Properties

| Physical State: Liquid  | Boiling Point: >300°F                  |  |
|-------------------------|--|--|
| Odor: Low               | Vapor Pressure: <0.1 mm Hg at 70°F     |  |
| Specific Gravity: 1.14  | Vapor Density: Heavier than air        |  |
| Volatile by Volume: <1% | Solubility in Water: Slight Solubility |  |

## 10. Stability and Reactivity

**Stability**: Stable under normal conditions.

Hazardous Polymerization: Will not occur.

Conditions and Materials to Avoid: Bases, strong oxidizing agents.

**Hazardous Decomposition Products**: Carbon monoxide, carbon dioxide.

## 11. Toxicological Information

**Chronic Exposure:** Allergic reaction and skin sensitization.

Mutagens:

Teratogens:

**Carcinogens:** 

No information available if blank.

## 12. Ecological information

Not available at this time.

## 13. Disposal Considerations

Dispose of in accordance with federal, state, and local regulations.

## 14. Transport Information

U.S. DOT IATA International Maritime
Shipping Name: Paint, Not regulated Paint, Not regulated Paint, Not regulated
Hazard Class: Not Regulated Not Regulated Not Regulated
UN ID Number: NA NA NA

UN ID Number:NANANAPacking Group:NANANA

# 15. Regulatory Information

#### **U.S. FEDERAL REGULATIONS:**

This Material Safety Data Sheet (MSDS) has been prepared in compliance with the federal OSHA Hazard Communication Standard 29 CFR 1910.1200.

#### SARA 311/312 Hazard Class:

Acute: Yes
Chronic: Yes
Flammability: No
Reactivity: No
Sudden Pressure: No

**SARA Reporting Requirements:** The components of this product are not subject to the reporting requirements of Sections 304 and 313 of Title III of the Superfund Amendments and Reauthorization Act.

SARA Threshold Planning Quantity: Not applicable.

**CERCLA Reportable Quantity (RQ):** Not listed

#### **U.S. STATE REGULATIONS:**

Rule 66 Status: Not photochemically reactive

#### **INTERNATIONAL REGULATIONS:**

**TSCA Inventory:** All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

Canada Domestic Substances List: All components of this product are listed on the Domestic Substances List

## **16.Other Information**

HMIS Codes: HEALTH 2

Fire 1
REACTIVITY 1